

539,196

10/539196

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(43) International Publication Date  
1 July 2004 (01.07.2004)

PCT

(10) International Publication Number  
**WO 2004/056031 A2**(51) International Patent Classification<sup>7</sup>: **H04L 9/00**

[US/US]; 1109 McKay Drive, M/S-41SJ, San Jose, CA 95131 (US).

(21) International Application Number:  
PCT/IB2003/006012(74) Common Representative: **KONINKLIJKE PHILIPS ELECTRONICS N.V.**; c/o LESTER, Shannon, 1109 McKay Drive, M/S-41SJ, San Jose, CA 95131 (US).(22) International Filing Date:  
17 December 2003 (17.12.2003)

(25) Filing Language: English


(26) Publication Language: English

(30) Priority Data:  
60/434,796 18 December 2002 (18.12.2002) US(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

(72) Inventor; and

(75) Inventor/Applicant (for US only): **EVOY, David***[Continued on next page]*(54) Title: **DEDICATED ENCRYPTED VIRTUAL CHANNEL IN A MULTI-CHANNEL SERIAL COMMUNICATIONS INTERFACE**

(57) Abstract: A data processing system, circuit arrangement, and method to communicate data over a multi-channel serial communications interface (14) using a dedicated encrypted virtual channel from among multiple virtual channels supported by the communications interface (14). Encryption for the dedicated encrypted virtual channel is provided by a hardware encryption circuit (34) that is coupled to the interface, such that encryption may be performed at a relatively low level, and with substantial protection from compromise, particularly along chip boundaries. In one particular application, access control may be provided for a digital data stream using a multi-chip access control scheme that relies on one chip (148) to provide access control over a received digital data stream, with another chip (150) utilized to process the digital data stream once authorized to do so. A secure, multi-channel serial communications interface between the multiple chips re-encrypts a digital data stream that has been decrypted on the access control chip (148) using hardware encryption logic (162) disposed on the access control chip (148), communicates the re-encrypted digital data stream over a dedicated encryption virtual channel supported by the multi-channel serial communications interface, and decrypts the re-encrypted digital data stream using hardware decryption logic (164) disposed on the other chip (150).

WO 2004/056031 A2